

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)


PCT

(10) International Publication Number
WO 2004/026709 A1

- (51) International Patent Classification⁷: **B65D 1/24**, 1/36, 25/04
- (21) International Application Number: PCT/US2003/029232
- (22) International Filing Date: 17 September 2003 (17.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/411,770 19 September 2002 (19.09.2002) US
- (71) Applicant (for all designated States except US): **HARVEST TECHNOLOGIES CORPORATION** [US/US]; 40 Grissom Road, Suite 100, Plymouth, MA 02360 (US).
- (72) Inventors; and
- (73) Inventors/Applicants (for US only): **ELLSWORTH, James, R.** [US/US]; 76 Magoun Path, Marshfield, MA 02050 (US). **MCGOVERN, Paul** [US/US]; 948 Winter Street, Hanson, MA 02341 (US).
- (74) Agents: **CLARK, Conrad, J.** et al.; Clark & Brody, 1750 K Street, NW, Suite 600, Washington, DC 20006 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: STERILE DISPOSABLE UNIT



(57) Abstract: A container designed for use as a disposable processing unit in a centrifuge includes first and second chambers connected by a bridge that allows transfer of fluid between the chambers. One of the chambers has a sloped floor that directs fluids to a smaller bottom portion for providing greater depth in the collected fluids. The container also includes cam surfaces that facilitate insertion of the container in a centrifuge in the desired orientation. As well, a key may be provided to ensure that the container is used in the correct centrifuge.



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

STERILE DISPOSABLE UNIT

TECHNICAL FIELD

[0001] This invention relates to the art of containers for use in treating fluids in a centrifuge. In particular, the invention relates to a disposable container having multiple chambers for processing blood and other physiological products in a centrifuge.

BACKGROUND

[0002] A decanting centrifuge using multi-chamber containers is known from US 5,707,331. According to that patent, a sterile processing disposable provides two chambers arranged adjacent each other so that a supernatant in one of the chambers may be decanted to the other of the chambers by gravity draining or centrifugal transfer techniques.

SUMMARY OF THE INVENTION

[0003] In accordance with the invention, a sterile processing disposable unit provides features that facilitate separation of fluids and ease of manufacture. The container comprises a base portion and a lid, both of which can be inexpensively molded, as by injection molding. The base portion comprises two chambers having a partition therebetween. The partition preferably comprises spaced walls connected at their tops, but it may be a single wall. The top of the partition is configured to allow supernatant fluids to flow over it and into the adjacent chamber.

[0004] The size of each chamber is designed to accommodate the fluids to be received in the particular chamber and to facilitate centrifugal separation of the components of the material in the chamber. One chamber is generally tubular and of a size to receive a predetermined volume of blood to be processed to produce autologous platelet rich plasma of

desired concentration. In preferred embodiments, this chamber is designed to receive 25 ml of blood in one case and 60 ml in another. The second chamber, which receives decanted plasma, may be smaller than the first chamber and further provides a still smaller bottom portion for receiving platelets separated from the decanted plasma to facilitate aspiration of these platelets. Preferably the cross section of the bottom portion is reduced to provide increased height of the platelets to further facilitate their aspiration.

[0005] The floor of the second chamber is preferably tapered to direct the separated platelets toward the bottom portion of the chamber so that they may be easily removed in a later step. In the preferred embodiment, the general configuration of the container is circular, and the tapered floor of the second chamber is preferably helical.

[0006] The helical configuration of the floor may also serve to orient the container in a centrifuge frame that receives the container. The frame is pivotally mounted to the centrifuge rotor by trunnions, and the helical floor of the container when not oriented will engage a part of the frame, such as an orienting projection on the side of the frame, as the user inserts the container in the frame. In the preferred embodiment, a skirt extends downward from the bottom surface to form a cam surface that engages the frame to orient the container in the frame during insertion. The skirt may be configured to provide the cam surface, and the inside floor of the chamber may have the same shape as the skirt or a different shape. This allows the floor of the second chamber to be configured to facilitate movement of the platelets toward the bottom portion of the chamber and the skirt to be configured to facilitate orientation of the container.

[0007] The container is also provided with exterior features that ensure the container is properly engaged in the frame. For example, the frame may be provided with a key that cooperates with a key on the container to ensure that the container is properly received in the frame. Further, the frame of a particular centrifuge may differ from that of

another centrifuge to ensure that a container designed specifically for one centrifuge is not accidentally used with another centrifuge.

[0008] The bottom portion of the second chamber is preferably configured to accommodate the orientation of the container when in the decanting orientation and in the orientation assumed during a second centrifugation whereby platelets are separated from the decanted plasma.

[0009] The lid for the container covers the base portion to provide sterility while allowing sterile access to the chambers. The lid, thus, includes a sterile access port for each chamber, and a vent for allowing egress of air displaced during introduction of blood into the first chamber and ingress of air during withdrawal of plasma and/or platelets from the second chamber.

[0010] The container also includes a floating divider that is received in the first chamber. The floating divider is designed to assume a position at or near the interface between plasma and red blood cells, which have been separated during an initial centrifugation process. The floating divider is cup-shaped and designed to provide a space between its periphery and the interior of the first chamber to allow passage of plasma, red blood cells, and other cellular components during centrifugation. The preferred divider also includes a central opening to allow passage of components during centrifugation. During decanting, the divider tilts about an axis transverse to the longitudinal axis of the chamber and thereby acts as a valve that stops decant of red blood cells that lie below the divider.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Figure 1 is a perspective of a container in accordance with the invention.

[0012] Figure 2 is a cross section taken along line 2-2 of figure 1.

[0013] Figure 3 is an assembly view of the container of figure 1.

[0014] Figure 4 is a perspective of the base portion of the container of figure 1.

[0015] Figure 5 is a side view of the base portion of figure 4.

[0016] Figure 6 is a top view of the base portion of figure 4.

[0017] Figure 7 is an enlarged detail of the portion of the container indicated in figure 2.

[0018] Figure 8 is a transverse cross section of a preferred floating divider.

[0019] Figure 9 is an enlarged detail of the portion of the divider indicated in figure 8.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0020] With reference to the figures, a preferred container 2 in accordance with the invention generally includes a base portion 4 and a lid 6. The base portion provides a first chamber 8 and a second chamber 10. The first chamber 8 is preferably cylindrical and formed by cylindrical outer wall 14, but may have other shapes. The first chamber receives a floating divider 12 that floats in the fluids to be introduced into the first chamber, and in the preferred embodiment, the divider 12 is cylindrical as well. It will be appreciated that the configuration of the first chamber must cooperate with that of the divider to allow the divider to float in the fluids.

[0021] Several walls intersect to provide the desired shape for the second chamber 10. A first outer wall 16 is generally cylindrical and extends at least partially around the first chamber 8. An inner wall 18 is also generally cylindrical and is joined to the outer wall 14 of the first chamber at their upper ends by a bridge portion 20.

[0022] The second chamber 10 includes a first floor portion 22 (see figures 3, 4, 6) that is arranged to slope toward a bottom portion 24 of the second chamber. Floor 22 is preferably helical. The bottom portion includes surfaces 26 and 28 that further reduce the

cross section of the bottom portion. It will be appreciated that the helical surface 22 directs platelets separated by centrifugation toward the bottom portion, and the reduced cross section of the bottom portion results in a reduced volume that provides greater vertical extent of the collected platelets to facilitate their removal from the second chamber by a cannula.

[0023] In the preferred embodiment, the surface 28 is oriented such that it is vertical when the container is subjected to centrifugation during collection of the platelets. For example, the bottom may be oriented at approximately 7° with respect to the upper surface of the base portion.

[0024] The lid 6 includes first access port 30 to provide sterile access to the first chamber and second access port 32 that provides sterile access to the second chamber. These ports are preferably made of flexible synthetic material and are inserted in holes in the material forming the remainder of the lid. Of course other constructions are possible, and they may be integral with the remainder of the lid. An air vent 33 is also provided to allow ingress and egress of air while maintaining sterility of the chambers.

[0025] The lid provides a central portion 34 that is raised with respect to an outer portion 36, the two being connected in part by an intermediate wall 38. During decanting, the plasma passes over the bridge 20 and through a passage 40 between the bridge 20 and the wall 38. This passage thus directs the plasma into the second chamber.

[0026] The exterior of the lower surface of the first chamber may be provided with a foot 42 to facilitate resting the container on a table or other flat surface.

[0027] Preferably, the container is adapted to be held in a particular orientation in the frame of a centrifuge. In one embodiment, the helical shape of the floor 22 of the second chamber acts also as a cam to assist an operator in orienting the container in the frame. Preferably, however, a skirt 44 extends from the floor to provide this camming action and allow the two features to have different shapes specifically adapted to the particular

purpose. In addition, a notch such as that shown at 46 is formed in the container between the upper ends of the floor 22, and that notch is designed to engage a similarly shaped element in the frame when the container is properly registered in the frame. The notch may be of various shapes and may include other features, such as a protuberance (not shown) that engages with a feature in the frame whereby containers having mostly common features may be distinguished from each other by the shape or configuration of the notch (e.g., width) or the presence of other features.

[0028] Figure 7 shows the preferred engagement between the upper edge 48 of the base portion and the periphery 50 of the lid. Upper edge 48 extends upward and flares outward slightly to engage periphery 50 in a fluid tight seal. This engagement is such that the lid may be attached to the base without cements or glues.

[0029] Figures 8 and 9 illustrate a preferred floating divider. This divider is cup shaped and fits in the first chamber such that a small space is provided between the outer surface 52 of the divider and the inner surface of the wall 14 forming the first chamber. Preferably, the bottom of the divider is provided with an opening 56 to allow passage of components being separated. This opening may be formed in a raised portion 58 of the wall bottom 54. In the preferred embodiment, the diameter of the opening is approximately 0.058 inch and the raised portion 58 is raised by about 0.02 inch. The entrance to the opening is chamfered at about 135 ° to the horizontal.

[0030] Modifications within the scope of the appended claims will be apparent to those of skill in the art.

We Claim:

1. A container comprising:
a base portion forming a first chamber and a second chamber connected by a bridge that allows fluid in said first chamber to flow to said second chamber when said container is in a predetermined orientation;
wherein one of said chambers includes a narrow bottom portion and a sloped floor portion arranged to direct said fluid to said bottom portion.
2. A container according to claim 1 wherein said sloped floor is helical.
3. A container according to claim 2 further comprising orienting means forming a cam surface for orienting said container.
4. A container according to claim 3 wherein said orienting means comprises a skirt extending from the bottom of said one of said chambers.
5. A container according to claim 2 further comprising a helical skirt extending downward from said one of said chambers.
6. A container according to claim 1 wherein said first and second chambers are connected by a bridge and said container further comprises a lid covering said first and second chambers, said lid having a raised portion that covers said first chamber and a recessed portion that covers said second chamber and an intermediate wall that forms a passage with said bridge for receiving said fluid.
7. A container according to claim 6 wherein said lid includes access means for providing sterile access to said first and second chambers.
8. A container according to claim 7 wherein said access means comprises a first access port in said raised portion and a second access port in said recessed portion.

9. A container according to claim 7 further comprising a floating divider in said first chamber.

10. A container according to claim 9 wherein said floating divider is cylindrical includes an opening allowing passage of fluids during centrifugation.

11. A container according to claim 10 wherein said floating divider includes a protuberance having said opening therein.

1/5

FIG. 1





FIG.2



SUBSTITUTE SHEET (RULE 26)

2/5




FIG.3

3/5

FIG.4





FIG.5



4/5

FIG.6





FIG.7



SUBSTITUTE SHEET (RULE 26)

5/5

FIG.8





FIG.9



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/29232

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : B65D 1/24, 1/36, 25/04

US CL : 220/501, 505

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 220/501, 505

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,172,826 A (CELAYA) 22 December 1992(22.12.1992), See the entire document.	1-11
X	US 5,676,275 A (KHATTAR) 14 October 1997(14.10.1997), See the entire document.	1-1
A	US 5,341,953 A (FORESTER) 30 August 1994 (30.08.1994)	
A	US 5,878,908 A (FOLEY) 09 March 1999 (03.09.1999)	

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

09 February 2004 (09.02.2004)

Date of mailing of the international search report

19 FEB 2004

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

Joseph Moy

Telephone No. (703)308-1148

Sheila H. Venev
Paralegal Specialist
Tech. Center 3700